

# 领鲜 多门时代



QOOLUX  
PERFORMANCE



Q2-SU225F  
Q2-SU225C



Q2-SU450F  
Q2-SU450C



Q2-SU670F  
Q2-SU670C

## COMMERCIAL STAINLESS STEEL AIR COOLING REFRIGERATOR



### 产品特点 / PRODUCT FEATURES

- 循环风流，快速制冷，柜内温度均匀；
- 门封内埋电热丝，减少凝露；
- 内胆圆角位设计，可彻底清除食物残渣，杜绝细菌滋生，符合卫生标准；
- 小于 90° 角门自动回归；
- 高精度电子温控，液晶数字清晰显示温度；
- 无氟环保制冷剂；

- Circulating air assures rapid cooling and even temperature;
- Heating wire inside door seal to defrost;
- Rounded internal corners for hygiene & easy cleaning;
- Autoregressive door;
- High quality digital controller and independent power switch;
- CFC & HCFC free, environmental friendly;

### LOCAL MAP



· High quality digital controller and independent power switch.



· Autoregressive door.



· Premier construction and material, applicable for hotels and deluxe restaurants;

| 型号<br>Model | 尺寸 (mm)<br>Size | 包装尺寸 (mm)<br>Packing Size | 净重 (kg)<br>N.W. | 毛重 (kg)<br>G.W. | 有效容积 (L)<br>Capacity | 温度范围 (°C)<br>Temp | 输入功率 (kw)<br>Input Power | 制冷剂<br>Refrigerant |
|-------------|-----------------|---------------------------|-----------------|-----------------|----------------------|-------------------|--------------------------|--------------------|
| Q2-SU225F   | 600x750x1950    | 705x830x2080              | 102             | 140             | 500L                 | -12~-18°C         | 0.48                     | R404A              |
| Q2-SU225C   | 600x750x1950    | 705x830x2080              | 102             | 140             | 500L                 | -2~+10°C          | 0.40                     | R134A              |
| Q2-SU450F   | 1250x750x2040   | 1330x830x2120             | 150             | 202             | 1000L                | -12~-18°C         | 0.63                     | R404A              |
| Q2-SU450C   | 1250x750x2040   | 1330x830x2120             | 150             | 202             | 1000L                | -2~+10°C          | 0.59                     | R404A              |
| Q2-SU670F   | 1880x750x2040   | 1960x830x2120             | 208             | 274             | 1600L                | -12~-18°C         | 1.50                     | R404A              |
| Q2-SU670C   | 1880x750x2040   | 1960x830x2120             | 208             | 274             | 1600L                | -2~+10°C          | 0.78                     | R404A              |